



*Industrial Protective Paints Ltd*



## TECHNICAL DATA SHEET

### PRODUCT NAME : ANTISLIP QUICK DRY CONCRETE FLOOR PAINT

A single pack, quick drying floor coating providing good durability and impact resistance. Moderate protection against solvents, salt and water damage are a positive advantage in the high risk areas which may be prone to pedestrian slippage. Anti-slip properties to meet most foot traffic requirements using a fine aggregated finish specially formulated to provide aesthetic and safe use. Suitable for medium duty commercial and industrial areas. Easy to apply by roller and brush and easy to repaint on high wear areas.

STANDARD COLOURS	Red oxide, slate and light grey and a limited range of other colours
DRY FILM APPEARANCE	Sheen, textured
SPREADING RATE	5-10 sq meters per ltr dependant on film thickness. (roller application)
TOUCH DRY @20°C	3 - 4 Hours
RECOATING TIME @20°C	24 Hours
TYPICAL WET FILM THICKNESS	85 - 130 Microns (per coat)
TYPICAL DRY FILM THICKNESS	50 - 75 Microns (per coat)
SOLIDS BY VOLUME	58% (ASTM D2697) +/-3% dependent on colour
V.O.C Information	420 g/litre (from formula to satisfy EU Solvent Emissions Directive)
APPLICATION TEMPERATURE	10 – 35 degrees C
APPLICATION METHODS	Brush or Roller
SUBSTRATES	Suitably cleaned & dry surfaces
THINNERS	Thinning not recommended – for cleaning use standard thinners.
FLASH POINT	>25°C
PACK SIZES	5 litre or 20litre pails
SHELF LIFE	12 Months

**KEY BENEFITS:** High performance, quick dry, nonslip safety product, formulated with high quality synthetic resins and complies with all current legislation at time of writing. SEE MSDS 3 for safety information

MOORVILLE COTTAGE FARM CELLARHEAD STOKE ON TRENT ST9 0DG  
TELEPHONE 01782 550733/303831 FAX 01782 550970/303227