



Industrial Protective Paints Ltd



TECHNICAL DATA SHEET

PRODUCT NAME : AIR DRYING INDUSTRIAL / AGRICULTURAL OXIDE

STANDARD COLOURS	RED, GREY, GREEN, BLACK, WHITE
DRY FILM APPEARANCE	GLOSS FINISH
SPREADING RATE	15 - 20 m² /litre @ 25 microns
TOUCH DRY @20°C	6 Hours
RECOATING TIME @20°C	16 Hours
AVERAGE WET FILM THICKNESS	30 - 50 Microns
AVERAGE DRY FILM THICKNESS	20 - 30 Microns
SOLIDS BY VOLUME	62%
VOLATILE ORGANIC COMPOUNDS	300 g/l (from formula to satisfy EU Solvent Emissions Directive) 295g/kg (from formula to satisfy EU SED regulations)
APPLICATION METHODS	Spray, Brush, Roller
SUBSTRATES	Suitably cleaned & dry surfaces
THINNERS	White Spirit
FLASH POINT	32°C
PACK SIZES	Barrels or 20 ltr, 5ltr, 1ltr cans
SHELF LIFE	12 Months

PRODUCT FEATURES:

Tough gloss surface finish, spray/brush/roller application, easy to use.

DESCRIPTION AND RECOMMENDED USES:

This product is a good quality general-purpose coating, made from high quality alkyd resins, formulated for ease of application, and is lead and chrome free.

MOORVILLE COTTAGE FARM CELLARHEAD STOKE ON TRENT ST9 0DG

TELEPHONE 01782 303831/550733 FAX 01782 550970/303227

E mail ipp@f2s.com