



Industrial Protective Paints Ltd



TECHNICAL DATA SHEET

PRODUCT NAME : Regal Prime & Seal

A tough, quick air drying finish suitable for direct to metal applications. Easy to apply by spray, roller and brush.

STANDARD COLOURS	Buff/Grey/Red
DRY FILM APPEARANCE	Matt
SPREADING RATE	5 m ² /litre
TOUCH DRY @20°C	1- 2 Hours
RECOATING TIME @20°C	24 Hours
TYPICAL WET FILM THICKNESS	25 - 45 Microns
TYPICAL DRY FILM THICKNESS	15 - 38 Microns
SOLIDS BY VOLUME	48% (ASTM D2697)
V.O.C Information	430 g/litre (from formula to satisfy EU Solvent Emissions Directive) 344g/kg (from formula to satisfy EU SED regulations)
APPLICATION TEMPERATURE	10 – 35 degrees C
APPLICATION METHODS	Spray (airless spray, air assisted spray 15-17 thou tip), Brush, Roller Suitably cleaned & dry surfaces
SUBSTRATES	
THINNERS	Xylene
FLASH POINT	25°C
PACK SIZES	210ltr Barrels or 20ltr pails
SHELF LIFE	12 Months

PRODUCT FEATURES:

Tough matt finish, brush/roller application, easy to use.

This product is a good quality matt/semi finish, quick dry, primer coat, made from high quality alkyd resins, formulated for airless spray, and is lead and chrome free.

MOORVILLE COTTAGE FARM CELLARHEAD STOKE ON TRENT ST9 0DG
TELEPHONE 01782 303831/550733 FAX 01782 550970/303227