



Industrial Protective Paints Ltd



TECHNICAL DATA SHEET

PRODUCT NAME : Regal Clear Finish

STANDARD COLOURS	None
DRY FILM APPEARANCE	Gloss
SPREADING RATE	10 m ² /litre
TOUCH DRY @20°C	1- 2 Hours
RECOATING TIME @20°C	12 Hours
TYPICAL WET FILM THICKNESS	45 - 75 Microns
TYPICAL DRY FILM THICKNESS	25 - 40 Microns
SOLIDS BY VOLUME	48% (ASTM D2697)
V.O.C Information	430 g/litre (from formula to satisfy EU Solvent Emissions Directive) 344g/kg (from formula to satisfy EU SED regulations)
APPLICATION TEMPERATURE	10 – 35 degrees C
APPLICATION METHODS	Spray (airless spray, air assisted spray 15-17 thou tip), Brush, Roller
SUBSTRATES	Suitably cleaned & dry surfaces
THINNERS	Xylene
FLASH POINT	25 °C
PACK SIZES	5Lts or 20ltr pails
SHELF LIFE	12 Months

PRODUCT FEATURES:

Regal Clear Finish is a fast dry, high gloss, clear, hard wearing protective finish. It's manufactured using a tough solvent based acrylic copolymer. It can be applied over both single and two pack flooring systems.

MOORVILLE COTTAGE FARM CELLARHEAD STOKE ON TRENT ST9 0DG
TELEPHONE 01782 303831/550733 FAX 01782 550970/303227