



Industrial Protective Paints Ltd



TECHNICAL DATA SHEET

PRODUCT NAME : QAD Primer Finish

A tough, quick air drying anti corrosive paint suitable for direct to metal applications such as SKIP and CONTAINER finishing. Easy to apply by spray, roller and brush.

STANDARD COLOURS	STANDARD COLOUR RANGE + BS / RAL RANGES
DRY FILM APPEARANCE	Available as GLOSS & SEMI GLOSS
SPREADING RATE	5.5 TO 8 m ² /litre
SURFACE DRY @20°C	15 - 30 Minutes
RECOATING TIME @20°C	1 Hour
TYPICAL WET FILM THICKNESS	120– 160 Microns
TYPICAL DRY FILM THICKNESS	65 - 90 Microns
SOLIDS BY VOLUME	56% +/- 3 dependent on colour (ASTM D2697)
V.O.C Information	430 g/litre (from formula to satisfy EU Solvent Emissions Directive) 344g/kg (from formula to satisfy EU SED regulations)
APPLICATION TEMPERATURE	10 – 35 degrees C
APPLICATION METHODS	Spray (airless spray, air assisted spray 15-17 thou tip), Brush, Roller
SUBSTRATES	Suitably cleaned & dry surfaces
THINNERS	Xylene
FLASH POINT	25°C
PACK SIZES	210ltr Barrels or 20ltr pails
SHELF LIFE	12 Months

PRODUCT FEATURES:

Tough gloss/semi surface finish, spray/brush/roller application, easy to use. This product is a good quality gloss/semi finish, quick dry, anti corrosive 1 coat, made from high quality alkyd resins, formulated for airless spray, and is lead and chrome free.

MOORVILLE COTTAGE FARM CELLARHEAD STOKE ON TRENT ST9 0DG

TELEPHONE 01782 303831/550733 FAX 01782 550970/303227

E mail ipp@f2s.com