



*Industrial Protective Paints Ltd*



## TECHNICAL DATA SHEET

### PRODUCT NAME: PARLOUR PAINT

A single pack, quick drying semi-gloss paint based on proven non-convertible resin technology with excellent durability and resistance to most cleaning chemicals and pressure washing. Available in a limited range of popular colours to combine a good cosmetic effect with an easy to clean and maintain finish. Suitable for general agricultural use where constant exposure to water and cleaning chemicals is likely. Easy to apply by brush or roller. Easy to recoat and with good cut edge coverage.

STANDARD COLOURS	Blue, white, slate and light grey and a limited range of popular colours
DRY FILM APPEARANCE	Sheen
SPREADING RATE	4 – 6 m <sup>2</sup> /litre (depending on surface profile)
TOUCH DRY @20°C	60 - 120 minutes
RECOATING TIME @20°C	8-10 Hours
TYPICAL WET FILM THICKNESS	150 - 200 Microns (per coat)
TYPICAL DRY FILM THICKNESS	75 - 100 Microns (per coat)
SOLIDS BY VOLUME	52% (ASTM D2697) +/-3% dependent on colour
V.O.C Information	412 g/litre
APPLICATION TEMPERATURE	6 – 35 °C
APPLICATION METHODS	Airless / conventional spray
SUBSTRATES	Suitable clean & dry surfaces
THINNERS	Thinning not recommended – for cleaning use standard thinners.
FLASH POINT	25°C
PACK SIZES	5 litre or 20litre pails
SHELF LIFE	12 Months

**KEY BENEFITS:** High performance, quick dry, formulated with high quality synthetic resins and environmentally friendly; meets RoHS and CONEG requirements at time of writing. Free from heavy metals. SEE MSDS 6 for safety information

MOORVILLE COTTAGE FARM CELLARHEAD STOKE ON TRENT ST9 0DG  
TELEPHONE 01782 550733/303831 FAX 01782 550970/303227