



Industrial Protective Paints Ltd



TECHNICAL DATA SHEET

PRODUCT NAME : POLYURETHANE CONCRETE FLOOR PAINT

A single pack, quick drying floor coating providing good durability and impact resistance with limited protection against solvents, salt and water damage. Available as a gloss or semi gloss finish in a range of colours specially formulated to provide good aesthetics and safe use. Suitable for light to medium duty commercial and industrial areas. Easy to apply by roller and brush and easy to repaint on high wear areas.

STANDARD COLOURS	Red oxide, slate and light grey and a limited range of other colours
DRY FILM APPEARANCE	Available as semi gloss
SPREADING RATE	5-10m ² /litre (roller application) @50μ
TOUCH DRY @20°C	8 Hours
RECOATING TIME @20°C	Min 24 Hours
TYPICAL WET FILM THICKNESS	90 - 135 Microns (per coat)
TYPICAL DRY FILM THICKNESS	50 - 75 Microns (per coat)
SOLIDS BY VOLUME	55% (ASTM D2697) +/-3% dependent on colour
V.O.C Information	430 g/litre (from formula to satisfy EU Solvent Emissions Directive)
APPLICATION TEMPERATURE	10 – 35 degrees C
APPLICATION METHODS	Brush or Roller
SUBSTRATES	Suitably cleaned & dry surfaces
THINNERS	Thinning not recommended – for cleaning use white spirit.
FLASH POINT	38°C
PACK SIZES	5 litre or 20litre pails
SHELF LIFE	12 Months

KEY BENEFITS: High performance, quick dry, nonslip safety product, formulated with high quality synthetic resins and complies with all current legislation at time of writing. SEE MSDS 3 for safety information

MOORVILLE COTTAGE FARM CELLARHEAD STOKE ON TRENT ST9 0DG
TELEPHONE 01782 550733/303831 FAX 01782 550970/303227