



Industrial Protective Paints Ltd



TECHNICAL DATA SHEET

PRODUCT NAME: QUICK DRY HIGH BUILD FLOOR PAINT

A single pack, quick drying high build floor coating providing good durability and impact resistance with moderate protection against solvents, salt, water and cleaning chemicals. Available as a semi-gloss finish in a range of colours specially formulated to provide good aesthetics and safe use. Suitable for medium to heavy duty commercial and industrial areas. Easy to apply by roller and brush and easy to repaint on high wear areas.

STANDARD COLOURS	Red oxide, slate and light grey and a limited range of other colours
DRY FILM APPEARANCE	Semi-gloss
SPREADING RATE	5 - 10m ² /litre (roller application) (10m ² @50μ, 5m ² @100μ)
TOUCH DRY @20°C	4 Hours
RECOATING TIME @20°C	24 Hours
TYPICAL WET FILM THICKNESS	85 - 135 Microns (per coat)
TYPICAL DRY FILM THICKNESS	50 - 100 Microns (per coat)
SOLIDS BY VOLUME	58% (ASTM D2697) +/-3% dependent on colour
V.O.C Information	420 g/litre (from formula to satisfy EU Solvent Emissions Directive)
APPLICATION TEMPERATURE	10 – 35 degrees C
APPLICATION METHODS	Brush or Roller
SUBSTRATES	Suitably cleaned & dry surfaces
THINNERS	Thinning not recommended – for cleaning use standard thinners.
FLASH POINT	25°C
PACK SIZES	5 litre or 20litre pails
SHELF LIFE	12 Months

KEY BENEFITS: High performance, quick dry, nonslip safety product, formulated with high quality synthetic resins and complies with all current legislation at time of writing. SEE MSDS 4 for safety information

MOORVILLE COTTAGE FARM CELLARHEAD STOKE ON TRENT ST9 0DG
TELEPHONE 01782 550733/303831 FAX 01782 550970/303227